


Needle roller bearing GBR303920-UU-IKO - GBR303920-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbr303920-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
47.625 (1 7/8)	GBR 303920 UU		240	47.625 (1 7/8)	61.912 (2 3/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
56.2	1	61 100	121 000	1 700		

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383040
Inside diameter	47.625 mm
Outside diameter	61.912 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE