


## Needle roller bearing GBR567232-U-IKO - GBR567232-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbr567232-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>88.900</b> (3 1/2)	<b>GBR 567232 U</b>		1 240	88.900 (3 1/2)	114.300 (4 1/2)	50.800 (2)
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$	$r$ as max	N	N	rpm		
106.3	1.5	170 000	347 000	900		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383194
Inside diameter	88.9 mm
Inside diameter	3 1/2" inch
Outside diameter	114.3 mm
Outside diameter	4 1/2" inch
Thickness	50.8 mm
Thickness	2" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE