


Needle roller bearing GBR1203320-U-IKO - GBR1203320-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbri203320-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
31.750 (1 1/4)	GBR1 203320 U		286	31.750 (1 1/4)	52.388 (2 1/8)	31.750 (1 1/4)			
		Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	Assembled inner ring		
B	F _w	Min.	Max.	r _{as max} ⁽¹⁾	N	N	rpm		
32.000	38.100 (1 1/2)	37	37.1	47.3	0.6	54 200	97 700	2 000	LRBZ 202420

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 Note⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383415
Inside diameter	31.75 mm
Outside diameter	52.388 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE