


Needle roller bearing GBRI243720-UU-IKO - GBRI243720-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbri243720-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | | |
|----------------------------|-----------------------|-----------------------------------|---------------------|-------------------------------------|---|--|----------------------|------------------------|------------------------------------|
| | With two seals | With one seal | | d | D | C | | | |
| 38.100 (1 1/2) | GBRI 243720 UU | | 330 | 38.100 (1 1/2) | 58.738 (2 1/4) | 31.750 (1 1/4) | | | |
| B | F _w | Standoff mounting dimensions - mm | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | |
| | | Min. | Max. | | | | | D _s Max. | r _{as max} ⁽¹⁾ |
| 32.000 | 44.450 (1 3/4) | 43.3 | 43.4 | 53.7 | 0.6 | 58 900 | 114 000 | 1 800 | LRBZ 242820 |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952383446 |
| Inside diameter | 38.1 mm |
| Outside diameter | 58.738 mm |
| Thickness | 31.75 mm |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE