


## Needle roller bearing GBR1243920-UU-IKO - GBR1243920-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbri243920-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number				Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals		With one seal			<i>d</i>	<i>D</i>	<i>C</i>	
<b>38.100</b> (1 1/2)	<b>GBR1 243920 UU</b>				400	38.100 (1 1/2)	61.912 (2 1/2)	31.750 (1 1/4)	
<i>B</i>	<i>F<sub>w</sub></i>	Standoff mounting dimensions - mm			Basic dynamic load rating <i>C</i> N	Basic static load rating <i>C<sub>0</sub></i> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		Min.	Max.	<i>D<sub>s</sub></i> Max.					<i>r<sub>as max</sub></i> <sup>(1)</sup>
32.000	47.625 (1 7/8)	43.3	45	56.2	1	61 100	121 000	1 700	<b>LRBZ 243020</b>

Notes: (1) Minimum allowable value of chamfer dimension *r*.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383477
Inside diameter	38.1 mm
Outside diameter	61.912 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE