

Needle roller bearing GBR1325228-U-IKO - GBR1325228-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbr1325228-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|----------------------------|-----------------------|---------------|---------------------|------------------------------|---------------|---------------|
| | With two seals | With one seal | | d | D | C |
| 50.800 (2) | GBR1 325228 U | | 950 | 50.800 (2) | 82.550 (3.25) | 44.450 (1.75) |

| B | F _w | Standard mounting dimensions mm | | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | |
|--------|----------------|---------------------------------|------|------------------------------------|-------------------------------|---|---|----------------------|-------------|
| | | Min. | Max. | r _{as max} ⁽¹⁾ | | | | | |
| 44.700 | 63.500 (2.5) | 58 | 61 | 75.7 | 1.5 | 93 300 | 179 000 | 1 300 | LRBZ 324028 |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952383538 |
| Inside diameter | 50.8 mm |
| Inside diameter | 2" inch |
| Outside diameter | 82.55 mm |
| Outside diameter | 3 1/4" inch |
| Thickness | 44.45 mm |
| Thickness | 1 3/4" inch |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE