


Needle roller bearing GBR1365628-U-IKO - GBR1365628-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbri365628-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
57.150 (2 1/4)	GBR1365628 U		1 050	57.150 ± 0.01	88.900 ± 0.01	44.450 ± 0.01

B	F _w	Standard mounting dimensions mm			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	D _s Max.				
44.700	69.850 ± 0.01	65	67	82	97 200	197 000	1 100	LRBZ 364428

Notes: (1) Minimum allowable value of chamfer dimension r.
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383545
Inside diameter	57.15 mm
Outside diameter	88.9 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE