

## Needle roller bearing NAFW102220-IKO - NAW102220-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nafw102220-iko>

**IKO**  
**NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE**  
With Inner Ring

Shaft dia. mm	Identification number	Mess (Ref.) g	Boundary dimensions mm					Standard mounting dimensions mm				
			d	D	C	r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	d <sub>s</sub> Max.	D <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>b</sub>	
10	NAFW 102220	40	10	22	20	0.3	14	17.6	20	12	13	14.6
Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup>		Assembled roller ring						
N		N		rpm		LRT 101420						
10 800		14 200		35 000								

Notes:  
(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952384382
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	20 mm
Packaging	1
Standard	No standard

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE