


## Needle roller bearing NAU4918-IKO - NAU4918-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nau4918-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings  
Full Complement Roller Bearings



Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> r <sub>s min</sub>	J	E <sub>w</sub>
90	—	NAU 4918	1 210	90	125	35	1.5	101	115.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>							
N	N	rpm							
79 500	130 000	4 000							

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952385648
Inside diameter	90 mm
Outside diameter	125 mm
Thickness	35 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE