

Needle roller bearing NAU4907-UU-IKO - NAU4907-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nau4907-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**

Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ min	J
35	—	NAU 4907UU	188	35	55	20	0.6	40
E _w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _g rpm					
	N	N		4 500				

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952385990
Inside diameter	35 mm
Inside diameter	1.378" inch
Outside diameter	55 mm
Outside diameter	2.165" inch
Thickness	20 mm
Thickness	0.787" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE