


## Needle roller bearing TRU426230-UU-IKO - TRU426230-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/tru426230-uu-iko>

**IKO**  
**ROLLER BEARINGS**

Caged Roller Bearings [With Seal]  
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r <sup>(1)</sup> min	J
42	—	—	TRU 426230UU	290	42	62	30	0.6	48
$E_w$	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> r/min						
56.5	N 34 600	N 57 800	4,000						

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAU and NLU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386140
Inside diameter	42 mm
Outside diameter	62 mm
Thickness	30 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE