


Needle roller bearing NAS5040-ZZ-NR-IKO - NAS5040-ZZ-NR-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nas5040-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
200		NAS 5040ZZNR	40.5	200	310	326	150	149	120	14.5

f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
5	3.5	1.5	242	1 310 000	2 650 000	500

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387178
Inside diameter	200 mm
Outside diameter	310 mm
Thickness	150 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE