


## Needle roller bearing NAS5068-UU-IKO - NAS5068-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nas5068-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
340	NAS 5068UU		180	340	520	—	243	241	—	—

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
—	6	2.5	404	3 370 000	7 560 000	300

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387314
Inside diameter	340 mm
Inside diameter	13.386" inch
Outside diameter	520 mm
Outside diameter	20.472" inch
Thickness	243 mm
Thickness	9.567" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE