


Needle roller bearing NAS5076-UU-IKO - NAS5076-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nas5076-uu-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
380	NAS 5076UU		200	380	560	—	243	241	—	—

f	c	r _s mm	J	Basic dynamic load rating C		Allowable rotational speed ^(*) rpm
				N	N ₁	
—	6	2.5	442	3 580 000	8 300 000	250

Notes^(*) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387352
Inside diameter	380 mm
Inside diameter	14.961" inch
Outside diameter	560 mm
Outside diameter	22.047" inch
Thickness	243 mm
Thickness	9.567" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE