


Needle roller bearing NAS5088-ZZ-IKO - NAS5088-ZZ-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nas5088-zz-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
440		NAS 5088ZZ	310	440	650	—	280	278	—	—

f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
—	8	3	516	4 570 000	10 900 000	200

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
Remarks: 1. The bearings with seals are provided with prepacked grease.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387413
Inside diameter	440 mm
Inside diameter	17.323" inch
Outside diameter	650 mm
Outside diameter	25.591" inch
Thickness	280 mm
Thickness	11.024" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE