

Needle roller bearing NBX6040-IKO - NBX6040-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nbx6040-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number														
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover		Mass (Ref.) g			
	NBX 6040						501							
60														
Boundary dimensions mm										Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm
F _w	D	D ₁	D ₂	L	H	r	r ₁ min.	d ₁	d ₂	Radial	Axial	Radial	Axial	
60	72	85	86.5	40	17	12	1	60	82	47 500	64 600	103 000	224 000	4 000

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390536
Inside diameter	60 mm
Inside diameter	2.362" inch
Outside diameter	72 mm
Outside diameter	2.835" inch
Thickness	40 mm
Thickness	1.575" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE