

Needle roller bearing NBXI2030Z-IKO - NBXI2030Z-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nbxi2030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification number										d	D	D ₁	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	NBXI 2030Z							
20	---	---	---	---	---	---	NBXI 2030Z				175	20	37	42

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 202520	
D ₂	L	B	H	I ₁	r _{max}	r _{min}	d ₁	d ₂	d ₃		Radial	Axial			Radial
43	30	20.5	11	9.5	0.6	0.3	25	40	24	20 000	22 700	32 100	60 700	9 000	LRT 202520

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390833
Inside diameter	20 mm
Outside diameter	37 mm
Thickness	30 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE