


Needle roller bearing NAXI3532Z-IKO - NAXI3532Z-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/naxi3532z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring



Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35	NAXI 3532Z	273	—	—	—	—	35	52	60

Boundary dimensions mm			Shoulder diameter mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring													
D ₂	L	H																		
61	32	20	13	10	0.6	0.3	40	52	39	29	400	26	900	54	100	50	000	5	500	LRT 354020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390932
Inside diameter	35 mm
Inside diameter	1.378" inch
Outside diameter	52 mm
Outside diameter	2.047" inch
Thickness	32 mm
Thickness	1.26" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE