


GE Rod end SB8513574-IKO - SB8513574-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/sb8513574-iko>

IKO

SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm							Permissible tilting angle degree
d		m	d	D	B	C	d_k	r_1 min	r_2 min	α
85	SB 8513574	4.29	85	135	74	63	125	0.6		6
Mounting dimensions mm			Dynamic load capacity C_d							
			Static load capacity C_s							
Min.	Max. ⁽¹⁾	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
89.5	100.5	130.5	116							

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k .
 Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
 2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391472
Inside diameter	85 mm
Outside diameter	135 mm
Thickness	74 mm
Type	-
Weight	4290 g
Lubrication	-
Dynamic load	772 kN
Static load	4630 kN
Packaging	-
Standard	-

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE