


GE Rod end SB115A-IKO - SB115A-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/sb115a-iko>

IKO

SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree
115	SB 115A	10.3	d	D	B	C	d _k	r ₁ min	α
			115	180	98	85	165	1	5

Mounting dimensions mm				Dynamic load capacity C _d	Static load capacity C _s
d _s	d _s	D _s	D _s	N	N
Min.	Max. ⁽¹⁾	Min.	Max.		
120.5	132.5	174.5	152	1 380 000	8 250 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
 Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
 2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391564
Inside diameter	115 mm
Outside diameter	180 mm
Thickness	98 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE