


## GE Rod end SB11518098-IKO - SB11518098-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/sb11518098-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree
	$d$	$D$	$B$	$C$	$d_k$	$r_1$	$r_2$	$\alpha$		
115	<b>SB 11518098</b>		10.3	115	180	98	85	165	1	5
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$						
$d_1$	$D_1$	$d_2$	$D_2$	N	N					
Min.	Max. <sup>(1)</sup>	Min.	Max.	N	N					
120.5	132.5	174.5	152	1 380 000	8 250 000					

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_k$ .  
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391571
Inside diameter	115 mm
Outside diameter	180 mm
Thickness	98 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE