


GE Rod end SB130A-IKO - SB130A-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/sb130a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | Mass (Ref.) kg | Boundary dimensions mm | | | | | | Permissible tilting angle degree α |
|---------------------------|-----------------------|-------------------------------------|------------------------------------|-------|-----|-----|-------|-------------------------|---|
| | | | d | D | B | C | d_k | r_1 mm ⁽¹⁾ | |
| 130 | SB 130A | 13.8 | 130 | 200 | 110 | 95 | 185 | 1 | 5 |
| Mounting dimensions mm | | Dynamic load capacity C_d N | Static load capacity C_s N | | | | | | |
| d_s | D_s | | C_d | C_s | | | | | |
| Min. Max. ⁽²⁾ | Max. Min. | N | N | | | | | | |
| 135.5 148.5 | 194.5 171 | 1 720 000 | 10 300 000 | | | | | | |

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952391601 |
| Inside diameter | 130 mm |
| Outside diameter | 200 mm |
| Thickness | 110 mm |
| Type | GE |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE