


## GE Rod end SB150A-IKO - SB150A-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/sb150a-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree $\alpha$	
			$d$	$D$	$B$	$C$	$d_k$ <sup>(1)</sup> $r_s$ mm		
150	<b>SB 150A</b>	17.0	150	220	120	105	205	1	5
Mounting dimensions mm		Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N						
$d_s$ Min.	Max. <sup>(2)</sup>		$D_s$ Min.	Max.	Min.	Max.			
155.5	166	2 110 000	214.5	189	12 700 000				

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391625
Inside diameter	150 mm
Outside diameter	220 mm
Thickness	120 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE