


## GE Rod end GE120ES-IKO - GE120ES-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge120es-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d <sub>s</sub>	r <sub>1</sub> <sup>(1)</sup> r <sub>1s</sub> min	r <sub>2</sub> <sup>(1)</sup> r <sub>2s</sub> min	α	α <sub>1</sub>
120	GE 120ES		8.12	120	180	85	70	160	1	1	6	4
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub>		Static load capacity C <sub>s</sub>								
d <sub>s</sub>		D <sub>s</sub>		N		N						
Min.	Max. <sup>(2)</sup>	Max.	Min.	N		N						
125.5	135.5	174.5	154	1 100 000		6 500 000						

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
 Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
 2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391991
Inside diameter	120 mm
Outside diameter	180 mm
Thickness	85 mm
Type	GE
Weight	8075 g
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE