


## GE Rod end GE200ES-IKO - GE200ES-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge200es-iko>

IKO

### SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
200	GE 200ES		26.1	200	290	130	100	250	1.1	1.1	7	6
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$								
$d_s$		$D_s$		N		N						
Min.	Max.(2)	Max.	Min.									
207	213.5	283	244	2 450 000		14 700 000						

Notes(1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392073
Inside diameter	200 mm
Outside diameter	290 mm
Thickness	130 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE