

GE Rod end GE70GS-2RS-IKO - GE70GS-2RS-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge70gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ r _{1s} min.	r ₂ ⁽¹⁾ r _{2s} min.	α	α ₁	
70	GE 70GS-2RS		3.00	70	120	70	45	105	1	1	16	14	
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s									
d _s		D _s		N		N							
Min.	Max. ⁽²⁾	Max.	Min.	N		N							
75.5	78	114.5	103	463 000		2 780 000							

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392431
Inside diameter	70 mm
Outside diameter	120 mm
Thickness	70 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE