


GE Rod end GE160GS-IKO - GE160GS-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge160gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
160	GE 160GS		25.4	160	260	135	80	225	1	1.1	16	14
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s		D_s		N		N						
Min.	Max.(2)	Max.	Min.									
165.5	180	253	221	1 770 000		10 600 000						

Notes(1)
(1) Minimum allowable value of chamfer dimensions r_1 and r_2
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392585
Inside diameter	160 mm
Outside diameter	260 mm
Thickness	135 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE