


GE Rod end GE260GS-IKO - GE260GS-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge260gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
260	GE 260GS		81.8	260	400	205	120	350	1.1	1.1	15	14
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s		D_s		N		N						
Min.	Max.(2)	Max.	Min.									
267	283.5	393	345	4 120 000		24 700 000						

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392677
Inside diameter	260 mm
Outside diameter	400 mm
Thickness	205 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE