

GE Rod end SBB76-2RS-IKO - SBB76-2RS-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/sbb76-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
120.650 (4 7/8)		SBB 76-2RS	11.6	120.650 (4 7/8)	187.325 (7 3/8)	105.56 (4.156)	90.47 (3.562)
d _k	Radial internal clearance mm Min./Max.	Mounting dimensions mm d ₁ (1) d ₂ (2) r ₁ max. (1) r ₂ max. (2)		Dynamic load capacity C _d N	Static load capacity C _s N		
173(6.811)	0.13 / 0.23	136.8	0.8 1.1	1 530 000	9 210 000		

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952393070
Inside diameter	120.65 mm
Outside diameter	187.325 mm
Thickness	105.56 mm
Type	GE
Weight	11600 g
Thread	Right-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE