

## GE Rod end GE60EC-2RS-IKO - GE60EC-2RS-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge60ec-2rs-iko>



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d <sub>k</sub>	r <sub>1</sub> mm	r <sub>2</sub> mm	α	α <sub>1</sub>
60	—	<b>GE 60EC-2RS</b>	1,10	60	90	44	36	80	1	1	—	3
Mounting dimensions mm			Dynamic load capacity C <sub>D</sub>		Static load capacity C <sub>S</sub>							
d <sub>s</sub>		D <sub>s</sub>		N		N						
Min.	Max. <sup>(1)</sup>	Max.	Min.	282 000		706 000						
65.5	66.5	84.5	79									

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark No oil hole is provided.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952393223
Inside diameter	60 mm
Outside diameter	90 mm
Thickness	44 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE