


GE Rod end GE110ES-IKO - GE110ES-IKO

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge110es-iko>

IKO

SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							Permissible tilting angle degree	
	Without seals	With seals		d_s	D	B	C	d_k	$r_{1s}^{(1)}$	$r_{2s}^{(1)}$	α	α_l
110	GE 110ES		4.94	110	160	70	55	140	1	1	6	4
Mounting dimensions mm				Dynamic load capacity C_d		Static load capacity C_s						
Min.		Max. ⁽²⁾		Max.		Min.						
115.5		121		154.5		138		755 000		4 530 000		

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952393773
Inside diameter	110 mm
Outside diameter	160 mm
Thickness	70 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE