


Yoke type track roller CRY32-VR-IKO - CRY32-VR-IKO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/yoke-track-roller/cry32-vr-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type/With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)									
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
15.875 ($\frac{5}{8}$)	CRY 32 VR		476	15.875 ($\frac{5}{8}$)	50.800 (2)	33.338(1.3125)	31.750 (1.25)						
				Shaft dia.				Basic dynamic load rating C	Basic static load rating C ₀				
				Push fit		Drive fit		Press fit					
				Min.	Max.	Min.	Max.	Min.	Max.				
				38.0(1.417)	600 (24)	15.857	15.867	15.873	15.883	15.883	15.893	45 700	80 600

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952398914
Inside diameter	15.875 mm
Outside diameter	50.8 mm
Thickness	33.338 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE