

Tapered roller bearing 33124-JR-JTEKT - 33124-JR-KOYO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/33124-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
120	200	62	62	48	482	785	1 800	2 400	33124JR					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
3FE	47.8	132	133	190	172	192	9	14	2	2	0.40	1.51	0.83	7.73

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411385
Inside diameter	120 mm
Outside diameter	200 mm
Thickness	62 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE