

Tapered roller bearing 32926-JR-JTEKT - 32926-JR-KOYO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32926-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
130	180	32	32	25	2	1.5	200	368	1 900	2 500	32926JR			
Dimension series to ISO355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
20C	31.4	140	141	171	165	174	6	7	2	1.5	0.34	1.77	0.97	2.42

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125669
Inside diameter	130 mm
Inside diameter	5.118" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	32 mm
Thickness	1.26" inch
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE