

Tapered roller bearing 32928-JR-JTEKT - 32928-JR-KOYO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32928-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
140	190	32	32	25	206	390	1 800	2 300	32928JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀		
20C	33.6	150	150	181	174	184	6	7	2	1.5	0.36	1.67	0.92	2.57

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125683
Inside diameter	140 mm
Outside diameter	190 mm
Thickness	32 mm
Weight	2500 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE