


## Tapered roller bearing 420-414-JTEKT - 420-414-KOYO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/420-414-koyo>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>2</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
40.000	88.501	26.988	29.083	22.225	3.6	1.6	98.2	112	4 900	6 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
420	414	16.9	52.0	46.0	77.0	80.0	3.6	1.6	0.26	2.28	1.25	0.465	0.325

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426792
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	88.501 mm
Outside diameter	3.484" inch
Thickness	26.988 mm
Thickness	1 1/16" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE