

Tapered roller bearing 342-332-JTEKT - 342-332-KOYO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/342-332-koyo>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> _{10v}	Grease lub.	Oil lub.
41.275	80.000	21.000	22.400	17.826	3.6	1.2	88.0	74.8	4 900	6 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
342	332	15.1	53.0	46.0	73.0	75.0	3.6	1.2	0.27	2.20	1.21	0.317	0.144

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426839
Inside diameter	41.275 mm
Outside diameter	80 mm
Thickness	21 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE