


Cam follower CF30-V-IKO - CF30-V-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf30-v-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm	Identification number								CF-V						
	Shield type				Sealed type				Mass (Ref.)	D	C	d ₁			
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	g	80					35	30	
30	CF30 V								1 870	80	35	30			
Boundary dimensions mm											Mounting dimension f Min. mm	Maximum tightening torque C N·m	Basic static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	g ₁	g ₂	f _{max}	(°)					N
M30 × 1.5	32	37	100	63	15	1	8	4	1	49		438	67 700	144 000	85 900

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440729
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	35 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE