


Cam follower CF30-1-VUU-IKO - CF30-1-VUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf30-1-vuu-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm	Identification number								Mass (Ref.) g	D	C	d ₁		
	Shield type				Sealed type									
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring							
30					CF 30-1 VUU				2 030	85	35	30		
Boundary dimensions mm														
G	G ₁	B _{max}	B _{1 max}	B ₂	B ₃	C ₁	g ₁	g ₂	f ⁽¹⁾ mm	Mounting diameter f _{min} mm	Maximum tightening torque C N·m	Basic static load rating C ₀ N	Maximum allowable static load C ₀ N	
M30 × 1.5	32	37	100	63	15	1	8	4	1	49	438	67 700	144 000	85 900

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440781
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	85 mm
Outside diameter	3.346" inch
Thickness	35 mm
Thickness	1.378" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE