

Cam follower CF8-UURM-IKO - CF8-UURM-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf8-uurm-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UUR

Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With tapered outer ring	With cylindrical outer ring					
8			CF-8	UURM	28.5	19	11	8	M 8x1

Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm	Maximum ignoring slope N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	7.1	4 250	4 740	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441054
Inside diameter	8 mm
Inside diameter	0.315" inch
Outside diameter	19 mm
Outside diameter	0.748" inch
Thickness	11 mm
Thickness	0.433" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE