


Cam follower CF12-1-IKO - CF12-1-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf12-1-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF

Stud dia. mm	Identification number				Max (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
12	CF 12-1				105	32	14	12	M12×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum lighting torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max	(°)					
13	15.2max	40.2max	25	6	0.6	6	3	0.6	21	21.9	7 910	9 790	9 790	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441290
Inside diameter	12 mm
Outside diameter	32 mm
Thickness	14 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE