


Cam follower CF16-IKO - CF16-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf16-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF

Stud dia. mm	Identification number				Max (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
16	CF 16				170	35	18	16	M16×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum lighting torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	r _s min					
17	19.6max	52.1max	32.5	8	0.8	6	3	0.6	26	58.5	12 000	18 300	18 300	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441337
Inside diameter	16 mm
Outside diameter	35 mm
Thickness	18 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE