


Cam follower CF20-UU-IKO - CF20-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf20-uu-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Max. (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
20				CF 20 UU	480	52	24	20	M20×1.5

Boundary dimensions mm										Bore diameter f mm	Maximum tightening torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max	(°)					
21	25.6max	66.1max	40.5	9	0.8	8	4	1	34	119	20 700	34 600	34 600	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441436
Inside diameter	20 mm
Outside diameter	52 mm
Thickness	24 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE