


Cam follower CF24-UU-IKO - CF24-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf24-uu-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
24				CF 24 UU	815	62	29	24	M24×1.5

Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	G ₂	f _{max} (°)	f _{min} mm	Maximum bearing torque N·m	Basic dynamic load rating C ₀	Basic static load rating C	Maximum allowable static load N	
25	30.6max	80.1max	49.5	11	0.8	8	4	1	40	215	30 500	52 600	52 000

Basic dynamic load rating C ₀	Basic static load rating C	Maximum allowable static load N
30 500	52 600	52 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441511
Inside diameter	24 mm
Outside diameter	62 mm
Thickness	29 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE