

Cam follower CF30-1-UUR-IKO - CF30-1-UUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf30-1-uur-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30	CF 30-1 UUR				2 030	85	35	30	M30×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{max}	(°)						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441627
Inside diameter	30 mm
Outside diameter	85 mm
Thickness	35 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE