


Cam follower CF8-VB-IKO - CF8-VB-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf8-vb-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



CF--VB

Stud dia. mm	Identification number								Mass (Ref.)			
	Shield type				Sealed type				g	D	C	d ₁
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring					
8	CF 8		VB						29	19	11	8

Boundary dimensions mm										Mounting dimension	Maximum tightening torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load	
G	G ₁	B _{max}	B _{1max}	B ₂	B ₃	C ₁	g ₁	B ₂	H _{max}	f ^(*) mm	N·m	C	C ₀	N	
M 8×1.25	10	12.2	32.2	20	—	0.6	—	—	4	0.3	13	6.5	8 170	11 200	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441757
Inside diameter	8 mm
Outside diameter	19 mm
Thickness	11 mm
Weight	36 g
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE