


Cam follower CF8-BUUM-IKO - CF8-BUUM-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf8-buum-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Hexagon Hole



CF-BUU

| Stud dia. mm | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G |
|-----------------|---|---|---|---|---------------------|----|----|----------------|-------|
| | Shield type With covered outer ring | Shield type With cylindrical outer ring | Sealed type With covered outer ring | Sealed type With cylindrical outer ring | | | | | |
| 8 | | | | CF 8 BUUM | 28.5 | 19 | 11 | 8 | M 8×1 |

| Boundary dimensions mm | | | | | | | | | | Mounting dimension f Min. mm | Maximum spinning torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|------------------------|---------|----------------|----------------|----------------|----------------|----------------|----------------|---|-----------------------|--|--------------------------------------|--|--|--|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | H | r _s Max | | | | | |
| 10 | 12.2max | 32.2max | 20 | — | 0.6 | — | — | 4 | 0.3 | 13 | 7.1 | 4 250 | 4 740 | 4 620 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952442655 |
| Inside diameter | 8 mm |
| Outside diameter | 19 mm |
| Thickness | 11 mm |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE