

Cam follower CF16-WBUUR-SG-IKO - CF16-WBUUR-SG-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf16-wbuur-sg-iko>

IKO

CAM FOLLOWERS

C-Lube Cam Followers With Cage / With Hexagon Hole



Stud dia. 12 to 20mm

Stud dia. mm	Identification number	Mass (Ref.) g	Boundary dimensions mm							
			D	C	d ₁	G	G ₁	B _{max}	B _{1max}	
16	CF 16 WBUUR/S	170 ^o	35	18	16	M16×1.5	17	19.6	52.1	
B ₂	B ₃	C ₁	g ₂	H	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable load N	
32.5	8	0.8	3	6	26	58.5	12 000	18 300	18 300	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443324
Inside diameter	16 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	220 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE