


Cam follower CFES6-B-IKO - CFES6-B-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfes6-b-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers **With Cage/With Hexagon Hole**



CFES-B

Stud dia. mm	Identification number								Mass (Ref.)							
	Shield type				Sealed type				g	D	C	d _i				
6	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	18.5	16	11	6				
	CFES 6 B															
Boundary dimensions mm																
G	G ₁	B	B ₁ max	B ₂ max	B ₃	C ₁	g ₁	g ₂	H	ε ^(°) Max	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M 6×1		8	12.2	28.2	16	—	0.6	—	3	0.3	0.25	11	2.7	3 660	3 650	1 980

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443379
Inside diameter	6 mm
Inside diameter	0.236" inch
Outside diameter	16 mm
Outside diameter	0.63" inch
Thickness	11 mm
Thickness	0.433" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE