


Cam follower CFES10-BUUR-IKO - CFES10-BUUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfes10-buur-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers **With Cage/With Hexagon Hole**



CFES-BUUR

Stud dia. mm	Identification number						Mass (Ref.) g	D	C	d ₁
	Shield type		Sealed type							
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
10					CFES 10	BUUR	45	22	12	10

Boundary dimensions mm										
G	G ₁	B	B ₁ max	B ₂ max	B ₃	C ₁	g ₁	g ₂	H	ε _{max} (°)
M10×1.25	12	13.2	36.2	23	—	0.6	—	4	0.3	0.3

Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
16	13.8	5 430	6 890	6 890

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443461
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	12 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE